


The product is designed, manufactured and tested in accordance with 97/23/EC directive and meets the applicable requirements listed below

	<p style="text-align: center;">AT1</p> <p style="text-align: center;">PART NUMBER 16508210</p>	<p style="text-align: center;">AT2</p> <p style="text-align: center;">PART NUMBER 16508310</p>
<p style="text-align: center;">VOLUME</p>	<p style="text-align: center;">2 L</p>	<p style="text-align: center;">5 L</p>
<p style="text-align: center;">WORKING PRESSURE</p>	<p style="text-align: center;">10 bar (max)</p>	<p style="text-align: center;">8 bar (max)</p>
<p style="text-align: center;">TEST PRESSURE</p>	<p style="text-align: center;">15 bar</p>	<p style="text-align: center;">12 bar</p>
<p style="text-align: center;">AIR PRESSURE</p>	<p style="text-align: center;">3,5 bar (max)</p>	<p style="text-align: center;">3,5 bar (max)</p>
<p style="text-align: center;">DESIGN TEMPERATURE</p>	<p style="text-align: center;">-10/+99 °C</p>	<p style="text-align: center;">-10/+99°C</p>
<p style="text-align: center;">PORTS</p>	<p style="text-align: center;">1/2" BSP</p>	<p style="text-align: center;">3/4" BSP</p>
<p style="text-align: center;">MEMBRANE MATERIAL</p>	<p style="text-align: center;">Butyl rubber</p>	<p style="text-align: center;">Butyl rubber</p>
<p style="text-align: center;">FLUID GROUP</p>	<p style="text-align: center;">2</p>	<p style="text-align: center;">2</p>
<p style="text-align: center;">CONFORMITY ASSESSMENT PROCEDURES</p>	<p style="text-align: center;">CAT I Mod. A</p>	<p style="text-align: center;">CAT I Mod. A</p>
<p style="text-align: center;">DIMENSIONS</p>	<p style="text-align: center;">Ø 125 mm x 239 mm (L)</p>	<p style="text-align: center;">Ø 165 mm x 306 mm (L)</p>